Multi-Gigabit SFP Fiber Module

WI-SFP10SC-3KM | WI-SFP10LC-3KM | WI-SFP10SC-20KM | WI-SFP10LC-20KM | WI-SFP20-20KM
WI-SFP20-10G-20KM | WI-SFP30 | WI-SFP30-10G

Overview

Wi-Tek Multi-Gigabit SFP Fiber Module is designed to extend transfer distances up to 20km with different fiber connectors. Single mode SFP module and multi-mode SFP module, which allows users to select the appropriate transceiver according to the required optical range for the network. The most common optical transceiver is 1310nm wavelength for a maximum of 20km with single mode fiber optics. Copper-based SFP modules primarily are 1000BASE-T and 1000BASE-TX SFP modules used in gigabit Ethernet networking within 100 meters. According to the transmission speed, Wi-Tek SFP module can provide the 10Gbps or 1.25Gbps modules.

Features

- Multi-Gigabit speed options as your needs
- Plug and play, zero configuration
- Durable metal casing, long life-time service
- Meet harsh environment with temperature: 0℃~70℃ (32℉~158℉)



Specifications






Model	WI-SFP10SC-3KM	WI-SFP10LC-3KM	WI-SFP10SC-20KM	WI-SFP10LC-20KM
Data Rate	1.25Gbps			
Max. Cable Length	3km		20km	
Wavelength	A: Tx1310nm/Rx1550nm B: Tx1550nm/Rx1310nm			
Power Supply	3.3V			
Media	Single-mode fiber (SMF)			
Connector	Simplex SC	Simplex LC	Simplex SC	Simplex LC
Others				
Safety & Emission	FCC&CE			
Environment	Operating Temperature: 0℃~70℃ (32℉~158℉) Storage Temperature: -40℃~80℃ (-40℉~176℉) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing			






Model	WI-SFP20-20KM	WI-SFP20-10G-20KM	WI-SFP30	WI-SFP30-10G
Data Rate	1.25Gbps	10Gbps	1000Mbps	10Gbps
Max. Cable Length	20km		100BASE-TX: UTP cat .5 or above (max. 100m) 1000BASE-T: UTP cat.5e or above (max. 100m)	100BASE-TX: UTP cat .5 or above (max. 100m) 1000BASE-T: UTP cat.5e or above (max. 100m) 10GBASE-T: UTP cat.6a or above (max. 30m)
Wavelength	1310nm		N/A	
Power Supply	3.3V			
Media	Single-mode fiber (SMF)		1*1000Mbps Ethernet Port	1*10Gbps Ethernet Port
Connector	Duplex LC		RJ-45 Port	
Others				
Safety & Emission	FCC&CE			
Environment	Operating Temperature: 0℃ ~70℃ (32℉~158℉) Storage Temperature: -40℃ ~80℃ (-40℉~176℉) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing	Operating Temperature: 0℃ ~70℃ (32℉~158℉) Storage Temperature: -40℃ ~80℃ (-40℉~176℉) Operating Humidity: 10%~90%		

Wireless-Tek Technology Limited
Address: Biaofang Technology Building 402, Bao'an street, Baoan District,Shenzhen City, Guangdong, China
Website:www.wireless-tek.com
Tel:86-0755-32811290
Email:sales@wireless-tek.com
Technical Support:tech@wireless-tek.com

Technical Support

Cloud Management

Company Website

©2022 Wireless-tek Technology Limited. All Rights Reserved.
Version,V1.0, updated 2022.4.07.
The information in this document is subject to change without notice.
Every effort has been made in the preparation of this document to ensure accuracy of the contents, but all statements, information, and recommendations in this document do not constitute a warranty of any kind, express or implied.